



*A member
of the
Canadian
Council of Land
Surveyors*

G O O D P R A C T I C E
R E S O L U T I O N S — A P R I L
1 9 8 7

1. It shall be considered good practice in establishing a section or quarter section corner from a witness monument to proceed as follows:

The said corner shall be defined by producing the line through the witness monument from the nearest monument on the same side of the witnessed corner. The corner in question shall be placed at the distance indicated for the witness monument.
2. It shall be considered good practice when surveying across sections in which either quarter line has been run to make an intersection with the surveyed quarter line and to place an iron post to define said point of intersection.
3. It shall be considered good practice, in the surveying of roads or other rights of way which run parallel and/or adjacent to established road allowances, to proceed as follows:
 - (a) If the limit of the right of way being posted is more than 30 metres from the posted boundary of the road allowance, then it shall be necessary to make an actual intersection with each surveyed line crossed.
 - (b) Where the limit of the right of way is 30 metres or less from the surveyed section line, said intersection may be made by an offset from the section line being paralleled. The bearing of the offset may be left to the discretion of the surveyor, but it is to be shown on the plan.
4. It shall be considered good practice, prior to registration of a subdivision plan, to plant 1 centimeter square iron bars not less than 50 centimeters long at the corners of each lot in a subdivision, excepting those lot corners which must be posted with Statutory Iron Posts under the provisions of the Alberta *Land Surveys Act*. The plan of survey shall have included in the legend a note stating that these iron bars have been established at all lot corners.
5. It shall be considered good practice when preparing plans of survey, to include on said plans notes with regard to the condition of monuments, and other data such as the position of iron posts with relation to corner fence posts.
6. It shall be considered good practice to show all calculated distances on plans in black followed by the abbreviation "(calc.)".
7. It shall be considered good practice when re-establishing lost corners in accordance with The Alberta Surveys Act, that due weight be given to the bearings as shown on the official or registered plan.
8. It shall be considered good practice to show on the plan of survey ties to iron posts placed at section or quarter section corners established from secondary evidence such as fence corners so that the position of that corner can be ascertained in relation to some supporting physical evidence on the ground.
9. It shall be considered good practice to obtain closure errors not exceeding 1 in 5000 in the surveyor's own work or 1 in 2500 in closing with section lines. In the event that in closing on older surveys this maximum is exceeded, sufficient information should be obtained to verify all new measurements taken.
10. It shall be considered good practice on surveys of roads or other rights of way which may terminate within the interior of a section to tie the terminal monument to some other known point in such a manner that a closure may be obtained from information shown on the plan.
11. It shall be considered good practice to place a note on the plan of survey describing the method used in establishing lost corners if the method is not otherwise clearly evident.
12. It shall be considered good practice, when conducting a right of way survey, to place iron posts in addition to those required by The Alberta Surveys Act, at intermediate points (preferably hilltops) such that any two consecutive points be intervisible and the distance between any two does not

- exceed one thousand metres.
13. It shall be considered good practice, when conducting a survey which requires the establishment of a boundary of an unposted railway right of way by accepting centre line of tracks at an end of curve or at a section line, to place an iron post on that tangent about 30 metres away from the end of curve or section line and -to tie the said iron post or posts to the survey being conducted so that the position accepted may be ascertained during subsequent surveys.
14. It shall be considered good practice, when establishing a boundary of an unposted railway right of way, the centre line of which is shown on the filed plan to be a spiraled curve, to replace the spiral with a compound curve in accordance with the following data:

Curve Data from Railway Plan					Replacement Curve Data
Degree and Radius of Central Curve	Length of Spiral	Spiral Angle	Delta of Replacement Curve	Replacement Curve Radius	Degree and Radius of Central Curve
2° 2864.9	180 168 120	1° 48' 1° 40' 1° 12'	1° 48' 1° 40' 1° 12'	3819.8 4331.2 3819.8	2° 2864.9
2° 30' 2292.0	210 200 150	2° 37.5' 2° 30' 1 ° 52.5'	2° 37.5' 2° 30' 1 ° 52.5'	3055.7 3359.2 3055.7	2° 30' 2292.0
3° 1910.1	240 234 180	3 ° 36' 3° 30' 2° 42'	3 ° 36' 3° 30' 2° 42'	2546.6 2765.7 2546.6	3° 1910.1
3° 30' 1637.3	270 204 210	4 ° 43.5' 3° 30' 3° 40.5'	4 ° 43.5' 3° 30' 3° 40.5'	2182.9 2412.2 2182.9	3° 30' 1637.3
4° 1432.7	300 231 240	6° 00' 4° 40' 4° 48'	6° 00' 4° 40' 4° 48'	1910.1 2024.7 1910.1	4° 1432.7
4° 30' 1432.7	300 264 270	6° 45' 6° 00' 6° 04.5'	6° 45' 6° 00' 6° 04.5'	1697.9 1786.0 1697.9	4° 30' 1432.7
5° 1146.3	300 248 300	7° 30' 6° 00' 7° 30'	7° 30' 6° 00' 7° 30'	1528.2 1677.2 1528.2	5° 1146.3
5° 30' 1042.1	300 279	8° 15' 7° 30'	8° 15' 7° 30'	1389.3 1499.7	5° 30' 1042.1

6°	300	9° 00'	9° 00'	1273.6	6°
955.4	310	9° 10'	9° 10'	1357.2	955.4
	360	10° 48'	10° 48'	1273.6	

15. It shall be considered good practice, when planting statutory iron posts in cultivated fields, to counter sink these posts below the depth of normal cultivation. When this is done or if posts are not planted in the ordinary way, a notation should be a notation on the plan of survey to that effect.
16. It shall be considered good practice; when conducting road or right-of-way surveys that intersect surveyed section or quarter section lines, to make the intersection by using the nearest section or quarter section corners on each side of the point of intersection. If the monuments at these corners are lost, they should be re-established giving due consideration to all available evidence.
17. It shall be considered good practice; to reference statutory iron posts by at least three bearing trees or with a marker post where the marker post does not interfere with the general public usage of the land or present a hazard.
 - (a) A marker post shall be placed 0.3 m from the iron post and shall be situated within a surveyed right-of-way or road allowance.
 - (b) Where (a) does not apply or is prevented by other circumstances the distance and direction from the iron post to the marker post shall be shown on the plan of survey, e.g.: "Mp. 1.5 m N."
 - (c) On control or W/S traverses, it is preferable that the iron post be referenced by at least three bearing trees. Marker posts to be used only in areas where suitable trees are not available.
18. It shall be considered good practice; when engaged to prepare a condominium plan. to perform the perimeter survey in accordance with the Surveys Act and to complete the following affidavit as the certification required by Section 8 of the Condominium Property Act:

AFFIDAVIT

I, _____ of _____, Alberta Land Surveyor, make oath and say:
 That the survey represented by this plan was made under my personal supervision;
 That the survey was made in accordance with good surveying practices and in accordance with the provisions of the Surveys Act;
 That the survey was performed between the dates of _____ and _____, 19 and
 that this plan is true and correct, and is prepared in accordance with the provisions of the Condominium Property Act and the Land Titles Act;
 That the building(s) situated on the parcel that is (are) the subject of this plan is (are) wholly within the external boundaries thereof; (in case of encroachment, this statement will be varied accordingly);
 SWORN before me at
 the _____ in the Province
 of Alberta this _____ day of _____, 19__.

 Alberta Land Surveyor

 A Commissioner for Oaths in
 and for the Province of Alberta

- 19.1. 1. In this standard
 - (a) "Alberta Land Surveyors' Real Property Report" means the survey and plan prepared in respect of a survey performed for the purposes of certifying the location of an improvement relative to the boundaries of a parcel of land;
 - (b) "improvement" includes any visible thing constructed or placed on, in or over land;
 - (c) "Parcel" means a unit of land described in an Alberta Land Surveyors' Real Property Report.
 - (d) "Surveyor" means an Alberta land surveyor.
2. A Surveyor performing a survey for the purpose of identifying, locating and illustrating

- improvements together with the extent of the parcel and encumbrances thereon, shall prepare an Alberta Land Surveyors' Real Property Report in accordance with this standard.
3. A Surveyor performing a survey for the purpose of preparing an Alberta Land Surveyors' Real Property Report shall locate and confirm sufficient survey monuments in order to define the boundaries of the parcel in accordance with the Surveys Act.
 4. When conducting a field survey for an Alberta Land Surveyors' Real Property Report, a surveyor shall:
 - 1) firstly perform research adequate to identify the parcel boundaries and encumbrances thereon, including obtaining a copy of the current Certificate of Title which shall be retained in his file.
 - 2) locate and confirm sufficient monuments in order to define the perimeter boundaries of the parcel in accordance with The Surveys Act.
 - 3) locate the main walls of all buildings located on the parcel relative to the boundaries thereof whether entirely or partially within the parcel together with any visible portions of the buildings which may extend beyond the main walls.
 - 4) locate relative to the boundaries of the parcel any other improvements situated on the parcel or adjacent lands which, in the opinion of the surveyor have a significant impact on the value, use or enjoyment of the parcel.
 5. When preparing a plan for an Alberta Land Surveyors' Real Property Report, a surveyor shall:
 - 1) indicate the legal description, municipality, and where available the municipal address of the parcel,
 - 2) designate the legal description of all lands adjoining the parcel.
 - 3) indicate prominently that the plan is an "Alberta Land Surveyors' Real Property Report".
 - 4) illustrate all improvements located pursuant to Section 4 hereof, with their dimensions and minimum distances from the boundaries of the subject parcel.
 - 5) indicate the nature of each improvement illustrated and where incomplete, the stage of construction of same.
 - 6) clearly and prominently identify any encroachment which may exist together with the amount of such encroachment.
 - 7) indicate the length and bearing of each boundary of the subject parcel.
 - 8) indicate the survey monuments used to define the perimeter boundaries in accordance with Section 4.2, together with the relationship of the said survey monuments to the perimeter boundaries of the parcel.
 - 9) illustrate, identify and dimension all easements which affect the parcel.
 - 10) place a note on the plan stating, "This plan is protected by copyright and no person may copy, reproduce, distribute, alter or otherwise make use of this plan in whole or in part without the written permission of _____, Alberta Land Surveyor.
 6. Good Practice Resolution Number 19 is hereby repealed and this standard shall be effective as of September 1, 1987.
 20. It shall be considered good practice; that all statutory iron posts placed be marked with the surveyor's corporation or partnership permit number or the membership number of individual surveyors not affiliated with a surveyor's partnership or limited company. A notation indicating the number stamped should be placed in the legend of the plan of survey.